

501 WD - PROFESSIONAL WET & DRY



FOOD INDUSTRY



WINE



CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING



- ✓ Easy filter replacement
- ✓ Compact and mobile
- ✓ Floating device to stop the suction when container is full

- ✓ Complete steel construction
- ✓ Accessory kit as standard
- ✓ Discharge hose for liquids



SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	1,15
Electrical protection	IP	CL 1
Max waterlift	mmH2O	2.500
Max air flow	m ³ /h	180
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74



FILTRATION UNIT

Filter Type		Star
Material - Efficiency	IEC 60335-2-69	Nuovo valore
Cleaning system		Manual



COLLECTION UNIT

Discharge system		Discharge hose
Capacity	lt.	50



VOLUME

Dimensions	cm	52x40x90h
Weight	kg	28



SUCTION UNIT

The suction is made by a carbon brush by-pass motor which is activated by an independent switch placed inside a robust metal motor head. The motor head is soundproofed by sound-absorbent material.



FILTRATION UNIT

The PPL polypropylene filter for liquids protects the motor from foam and other solid objects; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.



OPTIONALS

- ✓ STAINLESS STEEL CHASSIS
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ EARTH GROUNDING