

## 802 WD - PROFESSIONAL WET & DRY



BUILDING AND CONSTRUCTION



WINE



CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING



- ✓ Compact and mobile
- ✓ Two powerful by pass motors with independent cooling
- ✓ PPL filter for protection of motors from liquids and foam

- ✓ Accessory kit as standard
- ✓ Discharge hose for liquids



### SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	2,3
Max waterlift	mmH2O	2.500
Max air flow	m <sup>3</sup> /h	360
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76



### FILTRATION UNIT

Filter Type		Bag
Surface - Diameter	cm <sup>2</sup> -mm	8.000 - 420
Material - Efficiency	IEC 60335-2-69	Kit wet + Kit dry
Cleaning system		Manual



### COLLECTION UNIT

Discharge system		Discharge hose
Capacity	lt.	80



### VOLUME

Dimensions	cm	53x59x106h
Weight	kg	40



## SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



## FILTRATION UNIT

The PPL polypropylene filter for liquids protects the motor from foam and other solid objects; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



## COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.



## OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST